	Recommended Surfaces	voc	HAPs	COLOR	SHEEN (	COVERAGE
Transitional Primer	Interior/exterior previously painted walls, ceilings, wood and wood trim, fully cured plaster, stucco and masonry.	9 g/l	0	White	Flat	350 sf
New Wallboard Primecoat	New gypsum wallboard and textured sheetrock.	8 g/l	0	White	Flat	350 sf
MetalCoat Primer	Interior/exterior steel, galvanized metal and aluminum	0 g/l	0	White	Flat	350 sf
EcoLacq Sandable Primer	Unfinished wooden cabinetry, doors, paneling, furniture, and wood railings.	10 g/l	0	White	Flat	350 sf
Interior Paint	Properly primed interior walls and ceilings, properly cured and primed plaster (below 10 pH), masonry, woodwork and metal.	0 g/l	0	Tints	F P E SG	350 sf
Exterior Paint	Properly primed exterior walls, properly cured and primed plaster (below 10 pH), masonry, woodwork and metal.	8 g/l	0	Tints	Satin	350 sf
Concrete Floor Paint	Interior or exterior concrete, masonry, stone and brick.	110 g/l	0	Tints	SemiGlos	s 350 sf
EcoLacq	Unfinished or previously finished wooden cabinetry and doors, pan- eling, furniture, and wood railings.	10 g/l	0	Tints	G M	350 sf
Acrylacq	Raw wooden stained or previously painted cabinetry, doors, paneling, fur- niture, and wood railings.	59 g/l	0	Clear	GSM	350 sf
Polyureseal BP	Unfinished (or properly prepared and sanded previously finished) floors, wooden furniture and cabinetry and some vinyl type flooring.	99 g/l	0	Clear	GSM	350 sf
Polyureseal EXT	Unfinished exterior concrete floors, patio, brick walls, driveways, walk ways, pavers and wood.	9 g/l	0	Clear	GS	350 sf
AcriGlaze	Painted surfaces of plaster, wood, masonry and brick where a soft low luster finish and sealer is desired. Excellent medium for artist colors and universal tints. Ideal for restoring old finishes to their origi- nal brilliance, sealing and preserving painted work, faux finishing.	5 g/l	0	Clear	G M	350 sf
Safe Seal	Structural processed wood such as plywood, particle board and oriented strand board (OSB).	12 g/l	0	Clear	N/A	350 sf
Hard Seal	Interior previously painted walls, ceilings, woodwork, and cabinetry. Also effective on raw wooden surfaces, MDF, MEDEX, plywood or OSB	20 g/l	0	Clear	Gloss	350 sf
MexeSeal	Interior unpolished marble, limestone, granite, sandstone, slate, brick, terra cotta, concrete (brick, tile, precast panels, cast in place).	17 g/l	0	Clear	GS	350 sf

	Recommended Surfaces	voc	HAPs	COLOR	SHEEN	COVERAGE
Penetrating Water Stop	Porous mineral containing surfaces such as pavers, concrete slabs, block, stone, stucco and plasters under 10 pH.	0 g/l	0	Clear	Flat	200-600 sf
Water Shield	Vertical stucco, brick, block, and unglazed tile. Can also be used to add water repellency to exterior vertical wood siding.	0 g/l	0	Clear	Flat	350 sf
Grout Sealer	Unsealed tile grout. For previously sealed grout, conduct several small test patches for absorption and compatibility. Grout Sealer is compatible with all standard sanded or unsanded grouts.	0 g/l	0	Clear	Flat	200 sf per quart
Clear Penetrating Oil	Wood fencing, timberwork, furniture, decking.	200g/l	0	Amber	Flat	200-600 sf
Oil Wax Finish	Unfinished wooden cabinetry and doors, paneling, furniture, and wood railings and wooden floors.	250g/l	0	Amber	Flat	200-600 sf
Dynoseal	Seamless roofs, underlayment for shower stalls, pools, tubs and saunas. It is also recommended for use in repairing roofs, flashing, shingles and metal seams, and as a exterior vapor barrier against moisture from below-grade foundations. Also an effective radon barrier.	19 g/l	0	Black	Flat	100 sf
Dynoflex	New and old heating and air conditioning ducts, metal roof cracks, damaged asphalt shingles, mobile home roofs and similar areas.	0 g/l	0	Tan	Flat	350 sf
Roofguard	Properly primed roofs.	13 g/l	0	White	Flat	350
Almighty Adhesive	Wood and metal frame construction interior and exterior paneling. Bonds cove base, tub surrounds and fiberglass. Works on land- scape blocks, concrete, masonry, ceramic tile and ceiling tile. Excel- lent for decorative brick and stone, wood decking and sub-floor Installation	0 g/l	0	White	N/A	25 lf @.25"
3in1 Adhesive	Use indoors for adhering small/lightweight wall tiles up to 8" x 8" x 1/4" made of ceramic, also floor tiles made of ceramic, vinyl, parquet, and slate, and for any carpet application where a typical carpet adhesive would be used.	3 g/l	0	White	N/A	60-120 sf
All Purpose Cleaner	Stainless steel, fiberglass, porcelain, ceramic tile, chrome, painted sur- faces, wallpaper, wood, vinyl, steel, grout, concrete, fabric, plastic or any other hard non-porous surface.	0 g/l	0	Clear	N/A	Per dilution
Carpet Shampoo	All synthetic carpets and rugs.	0 g/l.	0	Clear	N/A	1200 sf per quart
Carpet Seal	All synthetic carpets and rugs.	0 g/l	0	Clear	N/A	300 sf
LockOut	All synthetic carpets and rugs.	0 g/l	0	Clear	N/A	300 sf